NOVACAT T RC collector Trailed disc mowers with cross conveyor belt





NOVACAT 307 T RC collector NOVACAT 3507 T RC collector

Your benefits at a glance

Perfect roller conditioner

- Driven by a drive belt on the bottom roller (1000 rpm) with a chain drive to the top roller.
- The upper roller is height adjustable.
- The gap between the rollers is adjustable.
- The conditioner pressure can be adjusted on both sides via coil spring adjusters.
- The robust central tube of the roller has a diameter of 5.51' / 140 mm and a wall thickness of 5.6 mm
- The polyurethane roller profile has an external diameter of 7.87' / 200 mm is vulcanised onto the central steel tube. The segments also cannot twist.
- The conditioner profiles are harder than rubber and therefore wear rates are reduced.
- The stub shafts of the roller are bolted and therefore easy to replace if necessary.
- · Chain lubrication via oil pump (lubricates when lifting at headlands).

Alois Pöttinger Maschinenfabrik GmbH Industriegelände 1 A-4710 Grieskirchen

Phone: +43 (0) 7248/600-0 Fax: +43 (0) 7248/600-2445

Pottinger UK

Redlake Trading Estate **Ivybridge** Devon PL21 0EZ - England Phone: 01752 891375 Fax: 01752 891379 www.pottingeruk.co.uk

Poettinger Canada Inc.

650, Route 112 St-Cesaire, J0L 1 T0, PQ Canada Phone: (450) 469-5594 Fax: (450) 469-4466

sales.canada@poettinger.ca Web: www.poettinger.ca

Poettinger US Inc. 107 Eastwood Road Michigan City, IN 46360

USA

Phone: 219 879-8597

E-Mail: sales.us@poettinger.us

www.poettinger.us

Poettinger Australia P/L

15 Fordson Road Campbellfield, VIC 3061 Australia

Phone: +61 3 9359 2969 Fax: +61 3 9359 6962

sales.au@poettinger.com.au www.poettinger.com.au

Importer for Ireland: T. Traynor & Sons Ltd. Cashel Road, Clonmel

Co. Tipperary Ireland Phone: 052/25 766

Fax: 052/25 802 e-mail: info@

Trailed disc mowers with cross conveyor belt

The new trailed disc mowers with roller-type conditioners and cross conveyor belts are unique on the market. The two conditioning rollers and additional accelerator roller ensure optimum crop flow onto the cross-conveyor belt.

Pöttinger guarantees 100% forage transfer to the conveyor belt, regardless of the crop and operating conditions.









NOVACAT	307 T RC collector	3507 T RC collector
Working width	9.97 ft / 3.04 m	11.35 ft / 3.46 m
Number of discs	7	8
Performance	8.9 acres / 3.6 ha/h	10.4 acres / 4.2 ha/h
Weight	5622 lbs / 2550 kg	6349 lbs / 2880 kg

All data not binding, features may vary from country to country.

Importer for New Zealand: Origin Agroup

PO Box 673, 57 Hautapu Road Cambridge - New Zealand Phone: 064 7 823 7582 Fax: 064 7 823 7583

e-mail:

info@originagroup.co.nz www.originagroup.co.nz



www.poettinger.at